



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : D21H 17/69, C04B 33/04	A1	(11) International Publication Number: WO 97/33040 (43) International Publication Date: 12 September 1997 (12.09.97)
(21) International Application Number: PCT/GB97/00648 (22) International Filing Date: 10 March 1997 (10.03.97) (30) Priority Data: 9604927.5 8 March 1996 (08.03.96) GB (71) Applicant (for all designated States except US): ALLIED COLLOIDS LIMITED [GB/GB]; Low Moor, P.O. Box 38, Bradford, West Yorkshire BD12 0JZ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): ALLEN, Adrian, Swinburn [GB/GB]; 6 Beechwood Drive, Skipton, North Yorkshire BD23 1TY (GB). STOCKWELL, John, Oliver [GB/GB]; 2 Cotswold Drive, Hightown, Liversedge, West Yorkshire WF15 8EG (GB). BLACK, Ian, James [GB/GB]; 10 Harbour Road, Wibsey, Bradford, West Yorkshire BD6 3RJ (GB). (74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: ACTIVATION OF SWELLING CLAYS AND PROCESSES OF USING THE ACTIVATED CLAYS (57) Abstract Alkaline earth bentonite can be activated by the use of sodium citrate or other organic sequestering agent as activator. Dry blends of the activator and the bentonite can be provided.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**Activation of Swelling Clays and Processes
of using the Activated Clays**

This invention relates to the activation of bentonite and to the use of the activated bentonite in paper making.

5 Bentonite is usually obtained initially as an alkali earth compound, for instance a calcium and/or magnesium form of bentonite. In order that it can perform satisfactorily, for instance in paper making, it is necessary to activate the bentonite by subjecting it to ion
10 exchange whereby calcium and/or magnesium is replaced by sodium or other alkali metal or ammonium ion.

The normal way of doing this is to mix the alkaline earth bentonite clay with an aqueous activating solution containing an alkali metal or ammonium compound. For
15 instance the clay may be provided as a powdered pre-blend of the alkaline earth metal clay and the alkali metal or ammonium compound and this pre-blend may be mixed into water and allowed to stand for sufficient time for ion exchange to occur whereafter it is diluted for use.
20 Alternatively the quarried alkaline earth bentonite can be added direct to an aqueous activating solution with mixing.

In practice, the activating compound which is conventionally used is sodium carbonate or sodium bicarbonate, typically in an amount of around 5 to 10% by
25 weight based on the weight of clay. The activation is conducted at the natural pH of the dispersion, around pH 10.

Other electrolytes are described in JP-A-6445754, as being added to promote dispersion. It is also known in
30 U.S. 4,613,542 and 4,624,982 to include sodium polyacrylate. Concentrates of bentonite with various alkali metal compounds are also described in EP 485124 and U.S. 5,266,538 and 5,391,228. The bentonite that is introduced into these concentrated slurries can initially
35 be in the form of sodium bentonite but EP 485,124 and U.S. 5,391,228 also mention making slurries by blending calcium bentonite and sodium carbonate activator with water and

sodium chloride. Paper making processes using bentonite with an anionic organic polymer are also described in EP 373306 and U.S. 5,015,334.

One problem with known activated bentonites (for instance the activated bentonite powders which are commercially available) is that the sodium carbonate or other activator which is included in them causes the bentonite (when mixed with water) to give a relatively high pH, for instance above pH 9 and often around pH 10. Accordingly it is necessary to handle the bentonite with the care associated with materials which do generate a pH of around pH 10.

Another problem is that the conventional sodium carbonate activator undergoes ion exchange during the activation process to form calcium carbonate, with the result that inorganic scale may be formed and deposited from aqueous compositions of these activated bentonites. This is a particular problem when the water in which the bentonite is being dispersed is, naturally, relatively hard.

Another difficulty with known activated bentonite powders is that it is sometime found to be rather difficult to make a stable aqueous dispersion of the powders. Again, it has been found that these difficulties of achieving a stable dispersion increase with increasing hardness of the water. Thus, when using relatively hard water, for instance having a hardness of above 10°dH and generally in the range 15° to 50°dH, various problems can arise.

Further, the performance of the bentonite, especially when used in paper making, can be less effective at lower pH values than at higher pH values, and in particular bentonite activated in conventional manner tends to be less effective in acid paper making processes (for instance when the cellulosic suspension has a pH of below 6.5 and often in the range 4.2 to 5.5) than when the suspension has higher pH values.

We have now discovered a new range of activators which can give improved performance.

According to a first aspect of the invention, we provide a dry clay composition comprising a blend of an alkaline earth bentonite swelling clay and an activating
5 amount of an alkali metal or ammonium salt of a sequestering agent selected from phosphonates, hydroxy carboxylic acids, amino carboxylic acids and poly carboxylic acids.

10 According to a second aspect of the invention, we provide a process of activating an alkaline earth bentonite swelling clay to an alkali metal bentonite swelling clay comprising mixing the alkaline earth swelling clay with an aqueous activating solution containing an ammonium or
15 alkali metal salt of a sequestering agent selected from phosphonates, hydroxy carboxylic acids, amino carboxylic acids and di- or tri- (or higher) carboxylic acids.

In both aspects of the invention, the sequestering agent is preferably introduced as a sodium salt.

20 In both aspects of the invention, the sequestering agent is preferably sodium citrate.

The resultant activated bentonites have several advantages. They are easier to handle since they are less alkaline. They can give better performance than the same
25 bentonite subjected to conventional activation with sodium carbonate at about pH 10. They can perform more effectively in paper making processes where conventional activated bentonites are less effective due to the pH or the presence of hardness salts. Thus conventional
30 bentonites tend to be less effective when the cellulosic suspension has pH below about 6.5, for instance in the range 4.2 to 5.5, but the activated bentonites obtained in the invention can perform very well in such suspensions without any significant loss of activity.

35 Conventional activated bentonites also may have inferior performance when the cellulosic suspension is made using relatively hard water, for instance having a hardness

above 10°dH and typically in the range 15°dH to 50°dH. Improved performance is obtained using the activated bentonites obtained in the invention in such hard waters. This improvement may be manifested by improved drainage rates or by reducing scale deposition or both.

The activation process can be conducted by separately introducing the swelling clay and the sequestering agent activator into the water, for instance by adding the swelling clay to a solution of the activator or by adding the activator to a dispersion of the swelling clay. In each of these alternatives, the swelling clay can be introduced as a powder or as a slurry.

Preferably, however, the process is conducted by mixing a pre-blend of the swelling clay and the activator with an appropriate amount of water. The pre-blend is preferably a powder but it can be a liquid composition containing the bentonite and the activator.

The amount of water present during the activation process is generally such that the swelling clay concentration during the process is from 2 to 8% or even up to 10%. Usually it is at least 3% and frequently it is not more than about 5 or 6%, with 4 or 5% often being preferred. These are the amounts which are typical for sodium carbonate activation processes and it is convenient that the same can be used in the invention.

However a further advantage of the activators used in the invention is that they will also cause good activation at a much wider range of concentrations and so good activation can be achieved at clay concentrations in the range 8 to 14 or 15%. Despite the clay activating during this process and thus potentially becoming very viscous, an advantage of the activators is that the resultant compositions still have adequately low viscosity and good fluid flow properties that they can be handled easily.

It is also possible to conduct the activation at even higher clay concentrations, for instance in the range 15 to 40%. We describe in our copending PCT application

(reference PRL03666WO filed even date herewith claiming priority from GB 9604950.7) concentrates having a clay concentration of 15 to 40% and which contain an activating amount of sodium citrate.

5 The sequestering agent seems to function by exchanging with the alkaline earth ions and fixing the exchanged calcium or magnesium ions in a form such that they cannot exchange back into the bentonite. The sequestering agent is usually in the sodium form as this is the preferred
10 cation which is introduced by ion exchange into the bentonite. However other activating cations can be used if desired, such as potassium or ammonium.

 Suitable phosphonates which can be used as the sequestering agent can be selected from any of the
15 phosphonates which are known for sequestering alkaline earth metal ions, such as the materials sold under the trade name Dequest.

 Suitable hydroxy carboxylic acids that can be used include materials such as sodium tartrate or gluconate but
20 the preferred material is sodium citrate. The free acid form can be used if required in preference to the water soluble salt.

 Suitable amino carboxylic acids include materials such as DTPA, NTA and EDDHA and EDTA.

25 Di- or tri- (or higher) carboxylic acids which can be used include malonic acid, succinic acid, glutaric acid, adipic acid and oxalic acid, usually as sodium salts. The acids (and all the sequestering agents) are preferably low molecular weight materials, for instance having a molecular
30 weight below 500 and are usually monomeric. The use of high molecular weight sodium polyacrylate in slurries is already known in EP 485124 and 4613542 and 4624982 but this does not give the benefits of the invention.

 The sequestering agent must be used in an amount
35 sufficient to give activation in the defined system and this will be found by routine experimentation. On a weight basis it is generally in the range 1 to 20% based on the

dry weight of bentonite, most preferably in the range 3 to 15%.

5 All these amounts assume that the sequestering agent is the only significant activating material in the composition. Blends of one or more of the sequestering agents may be used and blends of one or more of the sequestering agents with other beneficial activators such as sodium carbonate can be used if required. If sodium carbonate is present, then it may reduce the amount of
10 sequestering agent which is required. The amount of sequestering agent may have to be increased significantly if undesirable components such as sodium chloride are present to any significant extent and accordingly it is preferred that no deliberate additions of simple
15 electrolytes such as sodium chloride, sulphate or nitrate are made.

As the bentonite, one can use any of the anionic swelling clays that are conventionally referred to as bentonite-type clays or as bentonites. They are generally
20 smectites or montmorillonites, the latter being preferred. Suitable smectite or montmorillonite clays include Wyoming bentonite and Fullers Earth and various clays include those known by the chemical terms of hectorite and bentonite. The clay will be in the alkaline earth form, usually
25 calcium or calcium and magnesium form.

It is very well known to include bentonite in paper making processes for various purposes and the invention is applicable to all of these. For instance the bentonite may be included as a pitch dispersant.

30 One paper-making process to which the invention can be applied is a process in which bentonite is added to a cellulosic suspension, typically in an amount of 0.02 to 2% dry weight and a medium or high molecular weight (e.g., above 500000) polymeric retention aid is added
35 subsequently, generally after the last point of high shear (for instance just in front of the head box immediately prior to drainage). The high molecular weight polymer can

be non-ionic, anionic or cationic. The cellulosic suspension can be made from relatively pure pulp or from pulp having a relatively high cationic demand.

Processes of this type that are of particular value are those in which the pulp has a relatively high cationic demand and the polymer is substantially non-ionic or anionic and the paper product is preferably newsprint or fluting medium. Processes of this type in which the total filler content is relatively low are described in U.S. 4305781 and EP-A-17353 to which reference should be made for further details of suitable non-ionic or low ionic polymers and suitable cellulosic suspensions and which is hereby incorporated by reference. More highly anionic or cationic polymers may be used. These processes are of particular value when the cellulosic suspension contains de-inked waste. Suitable polymers and fillers (when the pulp is filled) are also described in EP-A-608989 and AU-A-63977/86.

The invention is of particular value when applied to microparticulate retention processes in which a polymeric retention aid is added to the aqueous suspension, the suspension is subjected to shearing and the bentonite is then added after the shearing, and often after the last point of high shear, for instance just prior to the head box prior to drainage. The polymer may be non-ionic or anionic but is often cationic.

The cationic polymer can be a natural material such as cationic starch but is preferably a substantially linear synthetic cationic polymer having molecular weight above 500,000. The amount of cationic polymer that is present in the dispersion at the time of shearing should be sufficient that flocs are formed by the addition of the polymer and the flocs are broken by the shearing to form microflocs that resist further degradation by the shearing but that carry sufficient charge to interact with the bentonite to give better retention and/or formation than is obtainable

when adding the polymer alone after the last point of high shear.

The shearing can be due merely to turbulent passage along a duct or can be due to passage through a centriscreen, a pump or other shear-applying device.

Preferred processes include those commercialised by the applicants under the trade mark Hydrocol and preferred processes are described in, for instance, U.S. patents 4753710, 4913775 and 4969976 all of which are hereby incorporated by reference. The optimum amount of polymer for any particular process can be determined by routine experimentation, and will depend inter alia on whether low or medium molecular weight cationic polymer, and/or dry strength resin, had been incorporated in the aqueous suspension at some earlier stage.

The activated bentonite of the invention can be used wherever activated bentonite is useful, for instance in pulp dewatering, paper sludge dewatering, liquid/solids separation processes, effluent clarification, inky waste water clarification and pitch fixing (in paper making processes). The activated bentonite can also be used in other industries which utilise activated bentonite, for instance in the preparation of bentonite for iron ore pelletisation or other mineral processing uses.

The following are some examples.

Example 1

5 parts by weight calcium bentonite was activated in 95 parts by weight of an aqueous solution containing the activator, and the amount of activator, specified below. In each instance, the amount of activator is expressed as a percentage based on the dry weight of bentonite. The products which were used were as follows.

A	-	sodium carbonate	- 6%
C	-	sodium citrate	- 17%
D	-	sodium EDTA	- 21%.

Example 2

The activated bentonites prepared in Example 1 are used in a laboratory simulation of the paper making process as described in US 4753710. In particular a thinstock of 0.5% bleached Kraft Fibre Furnish has added to it 500 g/t of a high molecular weight (intrinsic viscosity 6 dl/g) cationic polyacrylamide formed from 40% by weight dimethylaminoethyl acrylate quarternised by methyl chloride and 60% by weight acrylamide. The cellulosic suspension is sheared for 60 seconds 1,500 rpm, the activated bentonite is then added in the dose specified, the suspension subjected to gentle mixing in a baffled Britt jar and the Schopper Reigler drainage times recorded for 700 ml to drain from 1,000 ml of the thinstock. In this test, the lowest possible drainage time gives the best results, and low bentonite amounts are preferred.

In the following tables, the figures in the columns marked "Bentonite" are in g/t dry weight and the figures in the columns marked with a letter are the drainage time in seconds when using the specified amount of the activated bentonite identified in Example 1.

In this table, the column headed Ca represents the results using unactivated calcium bentonite.

Table 1

Bentonite	Ca	A	C	D
0	63	63	63	63
500	64	41	37	56
1000	62	25	25	49
2000	61	18	15	36
4000	58	14	11	20

This data shows that citrate activation (column C) can give results as good as or better than sodium carbonate activation as regards drainage time, and that adequate, but less satisfactory, results can be obtained using EDTA (column D).

CLAIMS

1. A dry clay composition comprising a blend of alkaline earth bentonite and an activating amount of an alkali metal or ammonium salt of a sequestering agent selected from
5 phosphonates, hydroxy carboxylic acids, amino carboxylic acids and di or tri carboxylic acids.
2. A composition according to claim 1 in which the salt is a sodium salt.
3. A composition according to claim 1 or claim 2 in which
10 the sequestering agent is sodium citrate.
4. A process of activating an alkaline earth bentonite comprising mixing the alkaline earth bentonite with an aqueous activating solution containing an activating amount
15 of an alkali metal or ammonium salt of a sequestering agent selected from phosphonate, hydroxy carboxylic acids, amino carboxylic acids and di or tri carboxylic acids.
5. A process according to claim 4 in which the sequestering agent is in the form of a sodium salt.
6. A process according to claim 4 in which the
20 sequestering agent is sodium citrate.
7. A process according to any of claims 3 to 6 conducted at a bentonite concentration of 2 to 14%.
8. A process of making paper comprising forming a
25 cellulosic suspension, mixing an activated bentonite dispersion into the suspension, draining water from the suspension to form a wet sheet and drying the sheet, wherein the activated bentonite dispersion has been made by a process according to claim 4, optionally followed by
30 dilution, or by mixing the composition of claim 1 into water.

INTERNATIONAL SEARCH REPORT

Int. .onal Application No
PCT/GB 97/00648

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 D21H17/69 C04B33/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 D21H C04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 391 228 A (CARROLL PAUL W) 21 February 1995 cited in the application Table 1, line 18 see column 3, line 15-23 ---	1-8
X	US 5 266 538 A (KNUDSON MILBURN I ET AL) 30 November 1993 cited in the application Table 5, line 16, Abstract see column 1, line 21-24 ---	1-8
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

22 May 1997

Date of mailing of the international search report

1 3. 06. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Naeslund, P

INTERNATIONAL SEARCH REPORT

Int onal Application No
PCT/GB 97/00648

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>DATABASE WPI Section Ch, Week 8844 Derwent Publications Ltd., London, GB; Class J01, AN 88-312148 XP002031287 & JP 63 230 550 A (NOGAMI S) , 27 September 1988 see abstract</p> <p>---</p>	1,4
X	<p>DATABASE WPI Section Ch, Week 8629 Derwent Publications Ltd., London, GB; Class A97, AN 86-186120 XP002031288 & JP 61 118 499 A (NEOS KK) , 5 June 1986 see abstract</p> <p>---</p>	1-6
X	<p>US 4 309 222 A (HOYT TH HAZEN L) 5 January 1982 Example</p> <p>---</p>	1-6
A	<p>EP 0 485 124 A (ALLIED COLLOIDS LTD) 13 May 1992 See the whole document</p> <p>---</p>	1-8
A	<p>EP 0 235 893 A (ALLIED COLLOIDS LTD) 9 September 1987 See the whole document & US 4 753 710 A (ALLIED COLLOIDS) 28 June 1988 & US 4 913 775 A (ALLIED COLLOIDS) 3 April 1990</p> <p>---</p>	1-8
A	<p>EP 0 223 223 A (BASF AG) 27 May 1987 See the whole document & AU 63977 86 A (BASF AG) 28 May 1997</p> <p>-----</p>	1-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. l. Application No

PCT/GB 97/00648

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5391228 A	21-02-95	US 5266538 A	30-11-93
		AU 4113893 A	29-11-93
		CA 2134785 A	11-11-93
		EP 0638053 A	15-02-95
		FI 945146 A	01-11-94
		JP 7506328 T	13-07-95
		WO 9322254 A	11-11-93
		AT 139515 T	15-07-96
		AU 669841 B	27-06-96
		AU 9176791 A	22-07-92
		BR 9107180 A	05-04-94
		CA 2102233 A	22-06-92
		DE 69120431 D	25-07-96
		DE 69120431 T	13-02-97
		EP 0563310 A	06-10-93
		ES 2088577 T	16-08-96
		JP 6508096 T	14-09-94
		WO 9211218 A	09-07-92

US 5266538 A	30-11-93	AT 139515 T	15-07-96
		AU 669841 B	27-06-96
		AU 9176791 A	22-07-92
		BR 9107180 A	05-04-94
		CA 2102233 A	22-06-92
		DE 69120431 D	25-07-96
		DE 69120431 T	13-02-97
		EP 0563310 A	06-10-93
		ES 2088577 T	16-08-96
		JP 6508096 T	14-09-94
		WO 9211218 A	09-07-92
		US 5391228 A	21-02-95

US 4309222 A	05-01-82	NONE	

EP 0485124 A	13-05-92	AT 126298 T	15-08-95
		AU 641054 B	09-09-93
		AU 8697591 A	04-06-92
		CA 2054829 A	06-05-92
		DE 69111982 D	14-09-95
		DE 69111982 T	23-11-95

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Application No

PCT/GB 97/00648

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0485124 A		ES 2075939 T	16-10-95
		JP 4281095 A	06-10-92
		NZ 240469 A	26-10-94
		US 5223098 A	29-06-93

EP 0235893 A	09-09-87	AU 578857 B	03-11-88
		AU 6811887 A	06-08-87
		CA 1259153 A	12-09-89
		FI 83349 C	22-08-96
		JP 6015755 B	02-03-94
		JP 62191598 A	21-08-87
		KR 9507186 B	03-07-95
		US 4753710 A	28-06-88
		US 4913775 A	03-04-90

EP 0223223 A	27-05-87	DE 3541163 A	27-05-87
		AU 578404 B	20-10-88
		AU 6397786 A	28-05-87
		CA 1278403 A	02-01-91
		JP 1059399 B	18-12-89
		JP 1572276 C	25-07-90
		JP 62125098 A	06-06-87
		US 4749444 A	07-06-88
